

SUREBONDER[®]

753 Adjustable Temperature Bulk Applicator

Specifications

Adjustable Temperature: 200°F to 500°F. (93°C. to 260°C.)
Watts Volts: 800 Watts, 120 Volts
Air Supply: 40 to 60 PSI
Adhesive Shape: Slats, Chips, Pellets, Bricks
Throat Depth: 6-1/2"
Dimensions: 18-1/4" High, 10-1/4" Wide, 8-3/8" Length
Weight: 35 Pounds
Tank Capacity: 2 Pounds
Viscosity Maximum: 20,000 CPS
Nozzles Orifices: .040", .080", .125"
Packaged: Box
Melt Rate: 5.5 lbs per hour
Flow Control: yes
Warm Up time: 20 minutes



753 Bulk Applicator

Industrial pneumatic bulk applicator that hold up to 2 pounds of hot melt adhesive. Time delay relay switch for the same amount of glue each time the foot treadle is depressed. Needle valve nozzle for complete shut off. Adjustable flow control switch. Ideal for pressure sensitive adhesive (peel-able) and EVA based adhesives.

American Chemical, Inc.
2201 North 2nd Street
Minneapolis, MN 55411 www.glueit.com
Phone 1-800-245-8348 Fax 1-800-845-8348