

DESCRIPTION

Fast-setting, water resistant high-tack adhesive for high-speed packaging and converting operations.

TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION

PROPERTY	VALUE
COLOR (WET)	UV White
COLOR (DRY)	Colorless
WEIGHT PER U.S. GALLON	9.1 lbs-mass/gallon
PH	5
SOLIDS	55.3 percent
VISCOSITY (RVF-3/20/77 DEG. F)	1,300 cPs
VISCOSITY (RVF-3/20/85 DEG. F)	1,100 cPs

CLEANUP PROCEDURE

Whenever possible, clean up product before it dries, using warm water. If dry, use hot water and scraper.

FREEZING SENSITIVITY

Store above 40 deg. F. (4 deg. C.).

STORAGE LIFE

For best results, we recommend that the product be used within three months.

EYE CONTACT AND PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. NO EXPECTED HARMFUL EFFECTS FROM INHALATION OF VAPORS. CONSULT MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. American Chemical, Inc. warrants that the product conforms with American Chemical, Inc. written specifications, and is free from defects. American Chemical, Inc. disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.

6/2008